



# SAFETY DATA SHEET

---

## SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

---

**Product ID:** .00539  
**Product Name:** PORT CITY DECK AND DOCK - MAHOGANY  
**Revision Date:** Oct 09, 2018 **Date Printed:** Oct 09, 2018  
**Version:** 2.0 **Supersedes Date:** Dec 13, 2016  
**Manufacturer's Name:** PORT CITY PAINTS  
**Address:** 473 West 17th Street Holland, MI, US, 49423  
**Emergency Phone:** 800-535-5053  
**Information Phone Number:** 616-396-1275  
**Fax:** 616-396-9654

---

## SECTION 2) HAZARDS IDENTIFICATION

---

### Classification

Acute aquatic toxicity - Category 3  
Aspiration Hazard - Category 1  
Carcinogenicity - Category 1B  
Chronic aquatic toxicity - Category 3  
Eye Irritation - Category 2  
Flammable Liquids - Category 2  
Germ Cell Mutagenicity - Category 1B  
Skin Irritation - Category 3  
Skin Sensitizer - Category 1  
Specific Target Organ Toxicity - Repeated Exposure - Category 1

### Pictograms



### Signal Word

Danger

### Hazardous Statements - Physical

H225 - Highly flammable liquid and vapor

### Hazardous Statements - Health

H304 - May be fatal if swallowed and enters airways

H350 - May cause cancer

H319 - Causes serious eye irritation

H340 - May cause genetic defects.

H316 - Causes mild skin irritation

H317 - May cause an allergic skin reaction

H372 - Causes damage to organs through prolonged or repeated exposure.

### **Hazardous Statements - Environmental**

H402 - Harmful to aquatic life

H412 - Harmful to aquatic life with long lasting effects

### **Precautionary Statements - General**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

### **Precautionary Statements - Prevention**

P273 - Avoid release to the environment.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P264 - Wash thoroughly after handling.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P270 - Do not eat, drink or smoke when using this product.

### **Precautionary Statements - Response**

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P370 + P378 - In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.

P321 - For specific treatment see section 4.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P314 - Get Medical advice/attention if you feel unwell.

### **Precautionary Statements - Storage**

P405 - Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

### **Precautionary Statements - Disposal**

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to

determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

**Acute toxicity of 4% of the mixture is unknown**

---

### SECTION 3) COMPOSITION, INFORMATION ON INGREDIENTS

---

CAS	Chemical Name	% By Weight
0064742-88-7	MEDIUM MINERAL SPIRITS	41% - 68%
0025265-77-4	2,2,4-TRIMETHYL PENTANEDIOL 1,3-MONOISOBUTYRAT	4% - 8%
0001335-30-4	ALUMINUM SILICATE HYDRATE	0.1% - 1.3%
0064741-65-7	ODORLESS MINERAL SPIRITS	0.1% - 0.9%
0055406-53-6	3-iodo-2-propynyl butylcarbamate	0.0% - 0.8%
0008052-41-3	STODDARD SOLVENT	0.0% - 0.3%
0000096-29-7	2-BUTANONE OXIME	0.0% - 0.3%
0000136-51-6	CALCIUM 2-ETHYLHEXANOATE	Trace
0000108-38-3	M-XYLENE	Trace
0000100-41-4	ETHYLBENZENE	Trace
0000106-42-3	P-XYLENE	Trace
0000095-47-6	O-XYLENE	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

---

### SECTION 4) FIRST-AID MEASURES

---

#### Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Eliminate all ignition sources if safe to do so.

#### Skin Contact

Take off all contaminated clothing, shoes, and leather goods (e.g., watchbands, belts). Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. If skin irritation or rash occurs: Get medical advice/attention.

Store contaminated clothing under water and wash before re-use (or discard).

#### Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

#### Ingestion

Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

---

### SECTION 5) FIRE-FIGHTING MEASURES

---

#### Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

#### Unsuitable Extinguishing Media

No data available.

#### Specific Hazards in Case of Fire

Vapors are heavier than air and may travel along the ground to ignition sources at locations distant from material handling point.

Vapor accumulations and spray mist may flash or explode if ignited.

Closed containers may rupture due to pressure buildup when exposed to extreme heat.

### **Fire-fighting Procedures**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

### **Special Protective Actions**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

---

## **SECTION 6) ACCIDENTAL RELEASE MEASURES**

---

### **Emergency Procedure**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

### **Recommended Equipment**

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

### **Personal Precautions**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

### **Environmental Precautions**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

### **Methods and Materials for Containment and Cleaning up**

Dike area to contain spill.

Absorb spill with inert absorbent.

---

## **SECTION 7) HANDLING AND STORAGE**

---

### **General**

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

### **Ventilation Requirements**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

### **Storage Room Requirements**

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

## SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION

### Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

### Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

### Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

### Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

A suitable, NIOSH-approved respirator and goggles should be worn when standing or grinding objects coated with this paint.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen
ALUMINUM SILICATE HYDRATE									1 (R)			A4
ETHYLBENZENE	100	435			1			20				A3
M-XYLENE	100	435			1			100	434	150	651	A4
ODORLESS MINERAL SPIRITS	500	2000			1							
O-XYLENE	100	435			1			100	434	150	651	A4
P-XYLENE	100	435			1			100	434	150	651	A4
STODDARD SOLVENT	500	2900			1			100	572			

Chemical Name	ACGIH Notations	ACGIH TLV Basis
ALUMINUM SILICATE HYDRATE	A4	Pneumococcosis; LRT irr; neurotoxicity
ETHYLBENZENE	A3; BEI	URT irr; Kidney dam (nephropathy); Cochlear

		impair
M-XYLENE	A4; BEI	URT & eye irr; CNS impair
ODORLESS MINERAL SPIRITS		
O-XYLENE	A4; BEI	URT & eye irr; CNS impair
P-XYLENE	A4; BEI	URT & eye irr; CNS impair
STODDARD SOLVENT		Eye, skin, & kidney dam; nausea; CNS impair

(C) - Ceiling limit, (R) - Respirable fraction, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, dam - Damage, impair - Impairment, irr - Irritation, LRT - Lower respiratory tract, URT - Upper respiratory tract

The information in this Section does not list components that might have relevant ACGIH Notations, ACGIH TLV Basis, OSHA TWA (ppm), OSHA TWA (mg/m3), OSHA Tables (Z1, Z2, Z3), OSHA Skin designation, ACGIH TWA (ppm), ACGIH TWA (mg/m3), ACGIH STEL (ppm), ACGIH STEL (mg/m3), ACGIH Carcinogen regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.

---

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

---

### Physical and Chemical Properties

Density	7.30874 lb/gal
% Solids By Weight	15.54230%
% VOC	61.57450%
Density VOC	4.50032 lb/gal
VOC Regulatory	4.47893 lb/gal
VOC Regulatory	536.71100 g/l

---

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	NA
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A

Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

---

## SECTION 10) STABILITY AND REACTIVITY

---

### Stability

Stable.

### Conditions to Avoid

Excessive heat.

### Hazardous Reactions/Polymerization

No data available.

### Incompatible Materials

Strong oxidizers.

### Hazardous Decomposition Products

May produce fumes when heated to decomposition.

Fumes may contain carbon monoxide and carbon dioxide.

---

## SECTION 11) TOXICOLOGICAL INFORMATION

---

### Skin Corrosion/Irritation

Causes mild skin irritation

### Serious Eye Damage/Irritation

Causes serious eye irritation

### Respiratory/Skin Sensitization

May cause an allergic skin reaction

### Germ Cell Mutagenicity

May cause genetic defects.

### Carcinogenicity

May cause cancer

### Reproductive Toxicity

No Data Available

### Specific Target Organ Toxicity - Single Exposure

No Data Available

### Specific Target Organ Toxicity - Repeated Exposure

Causes damage to organs through prolonged or repeated exposure.

### Aspiration Hazard

May be fatal if swallowed and enters airways

### Acute Toxicity

No Data Available

### Chronic Exposure

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

## Potential Health Effects - Miscellaneous

### 0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

### 0064741-65-7 ODORLESS MINERAL SPIRITS

Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

### 0064742-88-7 MEDIUM MINERAL SPIRITS

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, respiratory system, skin. This substance may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, lungs, reproductive system, skin. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with guinea pigs, dogs, or monkeys. Several studies evaluating petroleum workers have not shown a significant increase of kidney damage or an increase in kidney or liver tumors.

### 0000095-47-6 O-XYLENE

LC50 (rat): 5300 ppm (4-hour exposure); cited as 4330 ppm (6-hour exposure) (3)  
LC50 (mouse): 5630 ppm (4-hour exposure); cited as 4595 ppm (6-hour exposure) (3,4)  
LD50 (oral, rat): 3608 mg/kg (3,16)  
LD50 (dermal, rabbit): 20000 mg/kg (3)

### 0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)  
LD50 (oral, rat): 3.5 g/kg (1,3,5,10)  
LD50 (oral, rat): 4.72 g/kg (3,5,7,8)  
LD50 (dermal, rabbit): 17.8 g/kg (11)

### 0000106-42-3 P-XYLENE

LC50 (rat): 4740 ppm (4-hour exposure) (3)  
LC50 (mouse): 4800 ppm (4-hour exposure); cited as 3900 ppm (6-hour exposure) (1,4,6)  
LD50 (oral, rat): 4030 mg/kg (3); 4550 mg/kg (10)

### 0000108-38-3 M-XYLENE

LC50 (rat): 7330 ppm (4-hour exposure); cited as 5984 ppm (6-hour exposure) (3,17)  
LC50 (mouse): 6450 ppm (4-hour exposure); cited as 5267 ppm (6-hour exposure) (3)  
LD50 (oral, rat): 5011 mg/kg (3); 6660 mg/kg (3)  
LD50 (dermal, rabbit): 12180 mg/kg (3,17)

### 0008052-41-3 STODDARD SOLVENT

LC50 (rat): greater than 5500 mg/m<sup>3</sup> (880 ppm) (whole body exposure for 4 hours) (1)  
LC50 (rat): greater than 8200 mg/m<sup>3</sup> (1300 ppm) (2)  
LD50 (oral, rat): greater than 5 g/kg (1)  
LD50 (dermal, rabbit): greater than 3 g/kg (1)

---

## SECTION 12) ECOLOGICAL INFORMATION

---

### Bio-accumulative Potential

No data available.

### Persistence and Degradability

No data available.

### Mobility in Soil

No data available.

### Toxicity



Harmful to aquatic life

Harmful to aquatic life with long lasting effects

**Other adverse effects**

No data available.

---

**SECTION 13) DISPOSAL CONSIDERATIONS**

---

**Waste Disposal**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

---

**SECTION 14) TRANSPORT INFORMATION**

---

**U.S. DOT Information**

Proper Shipping Name: PAINT  
Identification Number : UN/NA 1263  
Hazard Class:3  
Packing group: II

**IMDG Information**

Proper Shipping Name: PAINT  
Identification Number : UN/NA 1263  
Hazard Class:3  
Packing group: II  
Marine Pollutant : No data available

**IATA Information**

Proper Shipping Name: PAINT  
Identification Number : UN/NA 1263  
Hazard Class:3  
Packing group: II

---

**SECTION 15) REGULATORY INFORMATION**

---

**REGULATORY INFORMATION**

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List

CAS	Chemical Name	% By Weight	Regulation List
0064742-88-7	MEDIUM MINERAL SPIRITS	41% - 68%	Canada_NPRI,DSL,SARA312
0091313-01-8	Non-Hazardous, Solid	16% - 27%	DSL,SARA312
0025265-77-4	2,2,4-TRIMETHYL PENTANEDIOL 1,3-MONOISOBUTYRAT	4% - 8%	DSL,SARA312
0001335-30-4	ALUMINUM SILICATE	0.1% - 1.3%	DSL,SARA312

	HYDRATE		
0064741-65-7	ODORLESS MINERAL SPIRITS	0.1% - 0.9%	Canada_NPRI,DSL,SARA312
0055406-53-6	3-IODO-2-PROPYNYL BUTYLCARBAMATE	0.0% - 0.8%	DSL,SARA312
0008052-41-3	STODDARD SOLVENT	0.0% - 0.3%	Canada_NPRI,DSL,SARA312,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000096-29-7	2-BUTANONE OXIME	0.0% - 0.3%	DSL,SARA312
0000136-51-6	CALCIUM 2-ETHYLHEXANOATE	Trace	DSL,SARA312
0000108-38-3	M-XYLENE	Trace	Canada_NPRI,DSL,HAPS,SARA312,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000100-41-4	ETHYLBENZENE	Trace	Canada_NPRI,DSL,HAPS,SARA312,CA_Carcinogen,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000106-42-3	P-XYLENE	Trace	Canada_NPRI,DSL,HAPS,SARA312,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000095-47-6	O-XYLENE	Trace	Canada_NPRI,DSL,HAPS,SARA312,WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS

The information in this Section does not list components that might have relevant CA\_Carcinogen, Canada\_NPRI, DSL, HAPS, SARA312, WI\_NR438 - WI\_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS regulatory values, if they are present at less than 10%. Please contact manufacturer for more information.

## SECTION 16) OTHER INFORMATION

### General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

### Other Special Consideration

\* There are points of differences between OSHA GHS and UN GHS. In 90% of the categories, they can be used interchangeably, but for the Skin Corrosion/Irritant Category and the Specific Target Organ Toxicity (Single and Repeated Exposure) Categories. In these cases, our system will say UN GHS.

### HMIS

Health	/ 2
FLAMMABILITY	2
Physical Hazard	0
Personal Protection	X

(\* ) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 2.0:

## **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.