

DESCRIPTION and USES

A high gloss enamel that features superior properties for interior or exterior painting. The finish provided by this Urethane-modified alkyd enamel is very durable and resistant to moisture, corrosion, mild chemicals, and weather. It is ideal for use on walls, floors, machinery and equipment. It can also be used successfully on non-immersion, fresh water marine equipment such as wooden or metal boats, docks and barges. GLO ENAMEL is available in a full range of colors, including OSHA Safety Colors.

SURFACE PREPARATION

All surfaces must be dry and free of dirt, grease, rust and loose paint. Rough surfaces should be smoothed with sandpaper. Glossy surfaces must be undercoated with Pro Flo Primer Undercoater or sanded to remove the gloss. Prime all bare surfaces with the recommended primer.

APPLICATION

Apply with brush, roller or spray. Use as supplied. Do not thin. Avoid application at temperatures above 90°F or below 50°F or when relative humidity is above 85%.

SAFETY INFORMATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

COLORS

This product is available in White, Black, all OSHA Safety Colors, Lawn Green, Nut Brown, Royal Blue and all *Color Folio* and *Color Studio* Colors.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Finish:	High Gloss
Vehicle Type:	Alkyd/Urethane
Pigments:	Titanium Dioxide or color pigments
Volume Solids:	45%
Coverage:	400 – 450 SF/Gallon
Dry Time:	
<i>Touch:</i>	3 – 5 Hours
<i>Recoat:</i>	8 Hours
Primer:	
<i>Masonry:</i>	44610 Sprayable Block Filler
<i>Drywall:</i>	44410 Quick Sealer
<i>Plaster:</i>	44110 Prime-All WB Primer
<i>Galvanized:</i>	44810 QD Rust Inhibitive Primer
<i>Steel:</i>	44917 Metl-Clad Metal Primer
<i>Wood:</i>	44010 Pro-Flo Primer-Undercoater 44510 Zip Prime-WB
VOC:	Less than 380 g/l
Clean Up:	Paint Thinner (Mineral Spirits)

PRODUCT CODE INFORMATION

40810	Glo-Enamel—White
40802	Glo-Enamel—102 Base
40803	Glo-Enamel—103 Base
40806	Glo-Enamel—106 Base
40820	Glo-Enamel—Bright Red
40830	Glo-Enamel—Royal Blue
40840	Glo-Enamel—Lawn Green
40850	Glo-Enamel—Nut Brown
40860	Glo-Enamel—Safety Yellow
40870	Glo-Enamel—Black
40880	Glo-Enamel—Safety Orange

RepcoLite Paints, Inc.
473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repcolite.com