

DESCRIPTION AND USES

Mira-Lac Pre-Catalyzed Lacquer is a product which offers the ease of application associated with lacquer coupled with performance characteristics similar to conversion varnishes. **Mira-Lac Pre-Catalyzed Lacquer** is a single component system that requires no additional catalyzation. It resists yellowing, meets or exceeds KCMA performance requirements and is recommended for use on fine furniture, interior doors and trim as well as kitchen cabinets.

SPECIFICATIONS

SURFACE PREPARATION: All wood surfaces to be finished must be clean, dry and free of contaminants such as oil or wax. Maple and birch should be sanded with 180 grit sandpaper prior to finishing. Moisture content of wood should be 7-9%. Oil-based stains should be allowed to dry a minimum of 24 hours before application of topcoat. Previously finished surfaces should be cleaned and thoroughly sanded with 220 grit sandpaper to ensure adhesion.

MATERIAL PREPARATION: **Mira-Lac Pre-Catalyzed Lacquer** is a single component product that does not require the addition of a catalyst. It is supplied ready-for-spray and does not require thinning. Stir container contents before use. Keep container closed when not dispensing.

APPLICATION: **Mira-Lac Pre-Catalyzed Lacquer** is designed for all types of spray application. Apply 1 coat of **740PW White Primer** or **740PB Black Primer** at 3-4 mils wet film build and topcoat with 1-2 coats of **Mira-Lac Pre-Catalyzed Lacquer**.

CLEAN UP: Use 910 Lacquer Thinner to clean dried product off equipment.

PRECAUTIONS

This product is intended for use by properly trained professionals in a controlled environment. Always pre-test the product or system on the substrate you will be using and under your line conditions to confirm application suitability and to avoid the need for costly refinishing.

COMPANION PRODUCTS

- 740 Series Products
- 800 Series Stains, Glazes and Toners
- 400 Series Stains and Fillers
- 910 Lacquer Thinner
- 950 Lacquer Retarder

PRODUCT CODES

740PW - White Primer

TECHNICAL DATA

VEHICLE TYPE: Pre-Catalyzed Lacquer

VOLUME SOLIDS: 32%

WEIGHT SOLIDS: 48%

DENSITY: 9.24 lbs/gal

VOC: 4.65 lbs/gal

REGULATORY VOC: 568 g/L

CLEAN UP SOLVENT: 910 Lacquer Thinner

COVERAGE: 517 square feet at 1 mil dry film thickness.

DRY TIME: Light sand in 30 minutes. Recoat in 45 minutes.

SHELF LIFE: 1 year shelf life when properly stored.

For complete safety information, refer to the SAFETY DATA SHEET for this product.

RepcoLite
Quality Paint Since 1946

RepcoLite Paints, Inc.
473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repcolite.com

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

Date: November 2015