

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: .46610
Product Name: WHITE ENDURA EXTERIOR FLAT
Revision Date: Jul 02, 2025 **Date Printed:** Jul 02, 2025
Version: 7.0 **Supersedes Date:** Jun 26, 2023
Manufacturer's Name: Repcolite Paints, Inc.
Address: 473 West 17th Street Holland, MI, US, 49423
Emergency Phone: 800-535-5053
Information Phone Number: 616-396-1275
Fax: 616-396-9654

SECTION 2) HAZARDS IDENTIFICATION

Classification

Carcinogenicity - Category 1B
Eye Irritation - Category 2A
Skin Irritation - Category 3
Skin Sensitizer - Category 1
Acute aquatic toxicity - Category 3
Chronic aquatic toxicity - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Health

H350 - May cause cancer
H319 - Causes serious eye irritation
H316 - Causes mild skin irritation
H317 - May cause an allergic skin reaction

Hazardous Statements - Environmental

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

- P273 - Avoid release to the environment.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P280 - Wear protective gloves, protective clothing, eye protection/face protection.
- P264 - Wash thoroughly after handling.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 - Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements - Response

- P308 + P313 - IF exposed or concerned: Get medical advice/attention.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical advice/attention.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.
- P321 - For specific treatment see section 4.
- P362 + P364 - Take off contaminated clothing. And wash it before reuse.

Precautionary Statements - Storage

- P405 - Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Acute toxicity of 17.6% of the mixture is unknown

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0007732-18-5	WATER	36% - 61%
0013463-67-7	TITANIUM DIOXIDE	8% - 20%
Proprietary	Acrylic Polymer	8% - 19%
0001332-58-7	KAOLIN	5% - 11%
0037244-96-5	NEPHELINE SYENITE	4% - 8%
PROPRIETARY	PROPRIETARY MIXTURE OF SUBSTANCES	2% - 5%
0000120-55-8	DIETHYLENE GLYCOL DIBENZOATE	0.1% - 0.9%
0027138-31-4	Propanol, oxybis-, dibenzoate	0.1% - 0.9%
0007631-86-9	SILICA, AMORPHOUS	0.1% - 0.8%
0021645-51-2	ALUMINUM HYDROXIDE	0.1% - 0.8%
0000057-55-6	PROPYLENE GLYCOL	0.1% - 0.6%
0008031-18-3	MAGNESIUM ALUMINUM SILICATE	0.1% - 0.5%
Proprietary	Polyurethane Resin	0.0% - 0.3%
0064742-46-7	MINERAL SEAL OIL	0.0% - 0.3%
0025265-77-4	2,2,4-TRIMETHYL PENTANEDIOL 1,3-MONOISOBUTYRAT	0.0% - 0.3%
0000124-68-5	2-AMINO-2-METHYL-1-PROPANOL	0.0% - 0.1%
0000330-54-1	DIURON	0.0% - 0.1%
0055406-53-6	3-iodo-2-propynyl butylcarbamate	0.0% - 0.1%
0013845-36-8	POTASSIUM TRIPOLYPHOSPHATE	Trace
0009004-62-0	CELLULOSE, 2-HYDROXYETHYL ETHER	Trace
0026530-20-1	3(2H)-Isothiazolone, 2-octyl-	Trace

CAS	Chemical Name	% By Weight
0000112-34-5	DIETHYLENE GLYCOL MONOBUTYL ETHER	Trace
0000077-99-6	1,3-PROPANEDIOL, 2-ETHYL-2 (HYDROXYMETHYL)-	Trace
0014808-60-7	SILICA, CRYSTALLINE	Trace
0001309-48-4	MAGNESIUM OXIDE	Trace
0002634-33-5	1,2-BENZISOTHIAZOL-3(2H)-ONE	Trace
0002682-20-4	2-METHYL-4-ISOTHIAZOLIN-3-ONE	Trace
0009005-00-9	Poly(oxy-1,2-ethanediyl), .alpha.-octadecyl-.omega.-hydroxy-	Trace
0027646-80-6	2-METHYLAMINO-2-METHYL-1-PROPANOL	Trace
0003811-73-2	SODIUM PYRITHIONE	Trace
0000556-67-2	OCTAMETHYLCYCLOTETRAISOLO	Trace
0000107-22-2	ETHANEDIOL	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

Get medical advice/attention if you feel unwell or are concerned.

Skin Contact

Rinse/wash with lukewarm, gently flowing water (and mild soap) for 5 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Eye Contact

If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention.

If you feel unwell or if concerned: Get medical advice/attention.

Ingestion

Rinse mouth. If you feel unwell or are concerned : Get medical advice/attention.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable Extinguishing Media

No data available.

Specific Hazards Arising from the Chemical

Product will not burn but may spatter if temperature exceeds the boiling point of water.

Dried solids can burn.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Keep unnecessary people away; Do not touch or walk through spilled material. Clean up immediately. Evacuate area and ventilate. Flammable/combustible material.

Protective Equipment

Positive pressure, full-face piece self-contained breathing apparatus SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Dike area to contain spill.

Absorb spill with inert absorbent.

SECTION 7) HANDLING AND STORAGE

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous.

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Keep from freezing.

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	ACGIH TWA (ppm)
DIETHYLENE GLYCOL MONOBUTYL ETHER								10(IFV)
DIURON								
ETHANEDIOL								
KAOLIN		[15]; [5 (a)];			1			
MINERAL SEAL OIL	500	2000			1			(L)[N159](L)[N800]
SILICA, AMORPHOUS	20 (b)	80 mg/m3 percent SiO2+2			1,3			
TITANIUM DIOXIDE		15			1			

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
DIETHYLENE GLYCOL MONOBUTYL ETHER						Hematologic, liver & kidney eff
DIURON	10			A4	A4	URT irr
ETHANEDIOL	0.1 (IFV)			A4	DSEN; A4	URT irr; larynx metaplasia
KAOLIN	2 (E,R)			A4	A4	Pneumoconiosis
MINERAL SEAL OIL	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	[A2][N159]A2[N800]]; [A4][N159]A4[N800]];	URT irr [N159]URT irr [N800]
SILICA, AMORPHOUS						
TITANIUM DIOXIDE	0.2 (R)(Nano), 2.5 (R)			A3		LRT irr; pneumoconiosis

(I) - Inhalable fraction, (IFV) - Inhalable fraction and vapor, (R) - Respirable fraction, A2 - Suspected Human Carcinogen, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, DSEN - Dermal sensitization, eff - Effects, irr - Irritation, LRT - Lower respiratory tract, URT - Upper respiratory tract

The information in this Section does not list non-hazardous components that might have relevant ACGIH TWA (mg/m3), ACGIH Carcinogen, ACGIH Notations, ACGIH TLV Basis, OSHA TWA (ppm), OSHA TWA (mg/m3), OSHA Tables (Z1, Z2, Z3), OSHA Carcinogen regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	10.83020 lb/gal
% Solids By Weight	48.42360%
% VOC	1.32715%
Density VOC	0.14373 lb/gal
VOC Regulatory	0.37518 lb/gal
VOC Regulatory	44.95790 g/l

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	NA
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

SECTION 10) STABILITY AND REACTIVITY

Chemical Stability

Stable.

Possibility of Hazardous Reactions/Polymerization

No data available.

Conditions To Avoid

Prevent from freezing.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

Burning of dried solids may give off oxides of carbon and nitrogen.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Prolonged contact may produce temporary reddening of skin.

Causes mild skin irritation

0000057-55-6 PROPYLENE GLYCOL

Contact can irritate the skin.

Serious Eye Damage/Irritation

Direct contact may cause eye irritation.

Causes serious eye irritation

0000057-55-6 PROPYLENE GLYCOL

Contact can irritate the eyes.

0000112-34-5 DIETHYLENE GLYCOL MONOBUTYL ETHER

Can be irritating to the eyes.

Respiratory/Skin Sensitization

May contain products that will irritate mucous membrane and respiratory tract.

May cause an allergic skin reaction

0000057-55-6 PROPYLENE GLYCOL

Prolonged or repeated contact can cause a skin rash dryness and redness.

0000112-34-5 DIETHYLENE GLYCOL MONOBUTYL ETHER

May cause dryness and cracking.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

May cause cancer

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

0000057-55-6 PROPYLENE GLYCOL

Exposure can cause headache, dizziness, lightheadedness, and passing out.

Specific Target Organ Toxicity - Repeated Exposure

0000057-55-6 PROPYLENE GLYCOL

Repeated high exposure may affect the kidneys.

Chronic Exposure

0014808-60-7 SILICA, CRYSTALLINE

Prolonged inhalation of respirable crystalline silica dust can result in lung disease (i.e. silicosis and/or lung cancer). Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.

Aspiration Hazard

Based on available data, the classification criteria are not met.

Potential Health Effects - Miscellaneous

0001332-58-7 KAOLIN

The following medical conditions may be aggravated by exposure: asthma, dermatitis. Repeated or prolonged inhalation may cause any of the following: lung injury.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.'

0014808-60-7 SILICA, CRYSTALLINE

Is an IARC, NTP or OSHA carcinogen. Repeated overexposure to crystalline silica may lead to x-ray changes and chronic lung disease. Inhalation of high dust concentrations may cause: breathing difficulties, lung injury. WARNING: This chemical is known to the State of California to cause cancer.

Acute Toxicity

Inhalation may produce symptoms of headache and nausea in poorly ventilated areas.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0002634-33-5 1,2-BENZISOTHIAZOL-3(2H)-ONE

LD50 (oral, rodent - rat): 1020 mg/kg, Toxic effects: Details of toxic effects not reported other than lethal dose value

0013463-67-7 TITANIUM DIOXIDE

LC50 (inhalation, Rat): >5.09 mg/L ; 4-hr exposure

Test atmosphere: dust/mist

No mortality observed at this dose.

LD50 Rat: > 5000 mg/kg

LD50 Hamster: > 10000 mg/kg

0026530-20-1 3(2H)-Isothiazolone, 2-octyl-

LD50 (oral, rodent - rat): 550 mg/kg, Toxic effects: Details of toxic effects not reported other than lethal dose value

LD50 (dermal, rodent - rabbit): 690 mg/kg, Toxic effects: Details of toxic effects not reported other than lethal dose value

0000330-54-1 DIURON

LD50 (oral, rodent - rat): 1017 mg/kg, Toxic effects : Behavioral - general anesthetic Behavioural - ataxia

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

Persistence and Degradability

0000112-34-5 DIETHYLENE GLYCOL MONOBUTYL ETHER

Readily biodegradable.

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000112-34-5 DIETHYLENE GLYCOL MONOBUTYL ETHER

The substance is not PBT / vPvB.

0000330-54-1 DIURON

LC50(Fish - Pimephales Promelas , 96 hrs) : 2.7971664 mg/L

EC50(Algae - Synechococcus sp. , 72 hrs) : 0.00055 mg/L EC50(Crustaceans - Mesocyclops aspericornis, 48 hrs): > 0.677 mg/L

0002682-20-4 2-METHYL-4-ISOTHIAZOLIN-3-ONE

LC50(Fish - Bluegill , 96 hrs) : 0.3 mg/L

0026530-20-1 3(2H)-Isothiazolone, 2-octyl-

LC50(Fish - Oncorhynchus mykiss , 96 hrs) : 0.05 mg/L

EC50(Crustaceans -Daphnia magna, 48 hrs): 0.107 mg/L

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Not regulated by the US Department of Transportation.

IMDG Information

No data available.

IATA Information

No data available.

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0007732-18-5	WATER	36% - 61%	TSCA - Toxic Substances Control Act (TSCA)
0013463-67-7	TITANIUM DIOXIDE	8% - 20%	SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Carcinogen, CA_Prop65_Type_Toxicity_Cancer
0001332-58-7	KAOLIN	5% - 11%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0037244-96-5	NEPHELINE SYENITE	4% - 8%	SARA312
PROPRIETARY	PROPRIETARY MIXTURE OF SUBSTANCES	2% - 5%	SARA312
0027138-31-4	Propanol, oxybis-, dibenzoate	0.1% - 0.9%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0007631-86-9	SILICA, AMORPHOUS	0.1% - 0.8%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000057-55-6	PROPYLENE GLYCOL	0.1% - 0.6%	SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA)
0064742-46-7	MINERAL SEAL OIL	0.0% - 0.3%	SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA)
0025265-77-4	2,2,4-TRIMETHYL PENTANEDIOL 1,3-MONOISOBUTYRAT	0.0% - 0.3%	SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA)
0000124-68-5	2-AMINO-2-METHYL-1-PROPANOL	0.0% - 0.1%	SARA312, VOC_exempt, TSCA - Toxic Substances Control Act (TSCA)
0000330-54-1	DIURON	0.0% - 0.1%	SARA313, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Carcinogen, CA_Prop65_Type_Toxicity_Cancer
0055406-53-6	3-IODO-2-PROPYNYL BUTYLCARBAMATE	0.0% - 0.1%	SARA313, SARA312, TSCA - Toxic Substances Control Act (TSCA)
0026530-20-1	3(2H)-Isothiazolone, 2-octyl-	Trace	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000112-34-5	DIETHYLENE GLYCOL MONOBUTYL ETHER	Trace	SARA313, Canada_NPRI, HAPS, SARA312, OC_HAPS, VOC, TSCA - Toxic Substances Control Act (TSCA), CA_TAC_Carcinogen
0002634-33-5	1,2-BENZISOTHIAZOL-3(2H)-ONE	Trace	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0002682-20-4	2-METHYL-4-ISOTHIAZOLIN-3-ONE	Trace	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0009005-00-9	Poly(oxy-1,2-ethanediyl), .alpha.-octadecyl-.omega.-hydroxy-	Trace	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000556-67-2	OCTAMETHYLCYCLOTETRASIL O	Trace	SARA312, VOC_exempt, TSCA - Toxic Substances Control Act (TSCA)
0003811-73-2	SODIUM PYRITHIONE	Trace	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000107-22-2	ETHANEDIOL	Trace	SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA)

The information in this Section does not list non-hazardous components that might have relevant CA_Carcinogen, CA_Prop65_Type_Toxicity_Cancer, TSCA - Toxic Substances Control Act (TSCA), SARA312 regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.



WARNING: This product can expose you to chemicals including TITANIUM DIOXIDE, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16) OTHER INFORMATION

General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 1
FLAMMABILITY	0
Physical Hazard	0
Personal Protection	X

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 7.0:

Revision Date: Jul 02, 2025

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.