

DESCRIPTION and USES

Woodmaster Oil Base Semi-Transparent Stain enhances the grain and texture of the wood surfaces to which it is applied. It penetrates deeply into the wood to provide lasting protection from sun and moisture. Ideal for both horizontal and vertical surfaces constructed of redwood, cedar or treated lumber. Not recommended for fir plywood.

PREPARATION

Surface Preparation: All cutting, gluing, and sanding of the wood should be done before coating. Surfaces to be stained must clean, dry, and free of contaminants such as dirt, oil or wax. If mildew is present, clean the surface with 1 part household bleach to 10 parts water solution. New pressure-treated wood should be allowed to dry for at least 30 days. New cedar should have the mill glaze removed through sanding or an oxalic acid-based cleaning/brightener product. Discoloration can be removed and the wood restored to its natural color by using a wood brightener. Rinse well after these treatments. Wear protective gloves, clothing, and goggles when working with bleach or wood brightener. Power washing to remove old or peeling stain is recommended. Allow 2 days for wood to dry after rain, rinsing, or power washing before staining.

APPLICATION

Stir thoroughly before and occasionally during use. Stains are best applied with a natural bristle brush, paint pad, or special stain applicator. Rolling and spraying may also be used, but the stain should be worked into the pores of the wood with a brush immediately after application with these methods. Maintain a wet edge by staining only a few boards at a time. Use as supplied. Do not thin.

CLEAN UP

Clean tools immediately after use with specified clean up solvent. Use same clean up solvent to clean dried product off equipment.

COLORS

A full range of custom colors are available.

REGULATORY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET for this product.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

| | |
|-----------------------|-----------------------------------|
| Finish: | Flat |
| Vehicle Type: | Soya Alkyd Resins and Linseed Oil |
| Weight Solids: | 36-37% |
| Volume Solids: | 31-32% |
| Density: | 7.1-7.2 lb/gal |
| Coverage: | 150 – 300 SF/Gallon |
| Dry Time: | |
| <i>Touch:</i> | 8 Hours |
| Clean Up: | Paint Thinner (Mineral Spirits) |
| VOC: | <550 g/L |
| Primer: | Self-prime |

Consult with a RepcoLite representative for additional recommendations of primers, sealers, and topcoats

PRODUCT CODE INFORMATION

45809 Woodmaster Oil Semi-Transparent Stain-#9 Base